



Office Furniture Slide Features

	Description
SLIDE TRAVEL	
2 Way Travel	Allows slide to move in both directions
Partial Extension	Slide travel is less than full extension
Full Extension	Slide travel equals length of slide in closed position
Over Travel Extension	Slide travel exceeds length of slide in close position
ATTACHMENT FEATURES	
Mounting Holes	Accommodates rivets, bolts/nuts, screws
Bayonet	Designed for tool-less, fast installation of metal storage
Belt-loops	Designed for tool-less, fast installation of metal storage
Brackets	Welded or snap-in brackets to support application
OPEN/CLOSE FEATURES	
Hold In Detent	Positive hold-in feature
Hold Out Detent	Positive hold-out feature
Self-Close	Effective closure of slide using spring technology
Soft-Close	Effective closure of slide with dampening technology
Push Open	Effective closure eliminates need for knobs, handles and pulls
Lock In / Lock Out	Mechanical latches keep drawers opened or closed
Anti-Tilt / INTERLOK™	Only one drawer opening at a time using Cable/Module system
Lever Disconnect	Cabinet and drawer slide members disconnect
Security Lock Integration	Leverage INTERLOK™ System to integrate with Security Lock System

	Description
EFFORT FORCE	
Engineered Polymers	Materials to support open/close features
Engineered Lubricant	Materials to deliver desired forces in actuating slide
FINISH OPTIONS	
Zinc Plating	RoHS compliant finish in clear zinc and black
E-Coating	RoHS compliant black finish
Power-Coat	RoHS compliant
STEEL OPTIONS	
Stainless Steel	For environments requiring high anti-corrosion components. Grade 304, 430
Cold-Rolled Steel	RoHS compliant
Hot-Rolled Steel	RoHS compliant
High Strength Steel	Hardened steel to provide extra strength without changing steel gauge
Galvanized	RoHS compliant
PACKAGING	
Bulk	Typically 10-40 slides per corrugated carton
Poly	Each slides placed in poly bag sleeve
Quantity	Slides disconnected to support dual installation work centers
Gaylord	Large quantity packaging for high volume applications
Returnable	Reusable totes to eliminate dunnage & support line-side production